

Equipment Rental Price List 2024		
ITEM	Description	Price (Day)
Black magic Pocket Cinema Camera 6K What is Included: Blackmagic Pocket Cinema Camera 6K (Body Only)	Effective Sensor Size 23.10mm x 12.99mm (Super 35) Lens Mount Active EF mount. Lens Control Iris, focus and zoom on supported lenses. Dynamic Range 13 Stops. Dual Native ISO 400 and 3200 Shooting Resolutions 6144 x 3456 (6K) up to 50 fps 6144 x 2560 (6K 2.4:1) up to 60 fps 5744 x 3024 (5.7K 17:9) up to 60 fps	85€
 SmallRig Cage Akku LP-E6 x 4 Blackmagic Netzteil mit DC-Anschluss Cfast 2.0 1TB 498MB/s Charger Smallrig Cage (Gehäuse) Belt Bag 	4096 x 2160 (4K DCI) up to 60 fps 3840 x 2160 (Ultra HD) up to 60 fps 3728 x 3104 (3.7K 6:5 anamorphic) up to 60 fps 2880 x 1512 (2.8K 17:9) up to 120 fps 1920 x 1080 (HD) up to 120 fps	
Canon 70 D Photo Camera	Sensor CMOS-Sensor APS-C 22,5 x 15,0 mm (Cropfaktor 1,6) 20,9 Megapixel (physikalisch) und 20,2 Megapixel (effektiv) Pixelpitch4,1 µm Fotoauflösung 5.472 x 3.648 (3:2) 1.920 x 1.080 (16:9)	
What is Included: Canon 70 D PhotoCamera (BodyOnly) Akku LP-E6 x4 Blackmagic Netzteil mit DC-Anschluss	Bildformate JPG, RAW Farbtiefe 42 Bit (14 Bit pro Farbkanal) Metadaten Exif (Version 2.21), DCF-Standard	35€
 SD Xtreme 64 GB Charger Bag 		

Heavy Tripod: NEEWER 73.6" horizontal tripod multi angle center column, ball head and center axis platform, aluminum camera tripod 360° swivel, 180° tilt for overhead/macro shots, max. load 22lb, TP27 18€ Heavy Weight Tripod Max Height 1,9m What is Included: Tripod Hotshoe Bag Cullmann - Nando - 52325-560M RW15 - Stativ -Travel Tripod: Aluminium - Reisestativ - Leichtgewicht -Schnellspanner - Kompakt Light Weight Tripod Max Height 1,6m What is Included: Tripod 10€ Hot shoe Bag Crafted from high-quality materials, the TILTA Stabilization System Advanced Ring Grip ensures durability and reliability, making it a long-lasting investment for any filmmaker. Its sleek and lightweight design adds minimal bulk to your setup, while providing maximum functionality and comfort during extended shooting sessions. DJI RS 2 is an advanced camera gimbal that stabilizes cameras for smooth, shake-free footage. Simply attach and balance your camera, then begin filming. DJI RS 2 integrates seamlessly with most cameras so you can access parameters and features directly on the 160€ device's full-color touchscreen. The Flowline Vest has Multiple Layers of Padding which ensures more support around the waist, What is Included: allowing you to mount large setups and shoot for DJI RS-2 Gimbal Pro + Raveneye longer duration comfortably. It has a flexible belt Tool Kit system & adjustable vest rods on sides which will Tilta ring grip enable a comfortable fit for all body types. Tlta Ring Grip Battery V Mount Tilta Wireless Dual Channel Lens Control Tilta Mini Nano Follow Focus 2x Smallrig 6700Wh Battery Carry Case *Hawaiian Shirt not included[©].

Dolly System: This tripod trolley is an excellent transport trolley for use with professional camera and video tripods, light 12€ stands, and background stands. All metal ball bearings swivel castors with rubber wheels for ultra smooth castors High performance construction for professional tripods Universal fully adjustable leg locks, one-step easy lock locking wheels What is Included: **Dolly Portable System** Bag Cine Lenses (Film): The Samyang DSLR prime lens kit 5 is EF mount and despite the name Produced in Germany. They are very fast and they are impressively compact and light so great for use on a gimbal. They have gears for follow focus or remote as well as iris gears. The lenses are designed to cover a full frame sensor as well as Super35mm and APS-C Technische Daten Samyang 50/1,5 VDSLR: - Brennweite: 50mm Technische Daten Samyang 14/3,1 VDSLR: - Brennweite KB: 14mm - Lichtstärke: 1:3,1 - Lichtstärke: 1:1,5 - Bildwinkel: 46.2 Grad / APS-C - 29 Grad Linsen / Gruppen: 14 / 10 Bildwinkel APS-C: 115,7 Grad - Filterdurchmesser: 77mm - Naheinstellgrenze: ca. 0,45m - Durchmesser / Länge: ca. 82 /74,7mm - Gewicht: ca. 575g Technische Daten Samyang 85/1,5 VDSLR: 85€ Technische Daten Samyang 24/1,5 VDSLR: - Brennweite: 85mm - Lichtstärke: 1:1,5 Brennweite KB: 24mm What's included: Lichtstärke: 1:1,5 Linsen / Gruppen:13 / 12 Bildwinkel KB / APS-C: 84,1° / 57,6° - Linsen / Gruppen: 9/7 - Bildwinkel: 35mm - 28,3 Grad / APS-C - 17,7 Grad 14mm CineLens T 3.1 Naheinstellgrenze: ca. 0,25m Filterdurchmesser: 77mm - Filterdurchmesser: 72mm 24mm CineLens T 1.5 - Naheinstellgrenze: ca. 1,1m Durchmesser / Länge: ca. 83mm / 97,5mm 35mm CineLens T 1.5 - Durchmesser / Länge: ca. 78mm / 80mm - Gewicht: ca. 570g 50mm CineLens T 1.5 Technische Daten Samyang 35/1,5 VDSLR: 85mm CineLens T 1.5 Brennweite KB: 35mm - Lichtstärke: 1:1,5 Linsen / Gruppen:12 / 10 Bildwinkel KB / APS-C: 63,1° / 40,8° Naheinstellgrenze: ca. 0,3m Filterdurchmesser: 77mm Lids & Hoods Carrying Case Lens Clean Kit Durchmesser / Länge: ca. 83mm / 111,5mm Gewicht: ca. 700g Tackle a variety of subjects from landscape to portrait Canon 24-70mm (Events Video, to documentary and Events. Photo): The EF 24-70mm f2.8 USM is an ideal standard lens for your EF Camera, featuring wide angle, standard and telephoto focal lengths and a constant f.28 maximum aperture that doesn't change as the lens is zoomed, making it perfect for live and fast shooting of documentary, events, live sessions and also 25€ journalism. What's included: Lens Lids + Sun Hood + Cloth Bag

Canon Lens Kit (Photography):



What's included:

- Tamron AF 70-300 F4.0-5.6 Di LD Macro 1:2 62
- Canon 24mm "Pancake" 2.8 EF-S
- Canon 50mm 1.8 EF
- Canon 18-55 3.5-5,6F EF-S
- Lids + Bag
- Clean Kit

Today, Canon still uses this EF mount for their professional "L-Series" lenses. Because of this, older film camera lenses with the EF Canon mount can still work on DSLRs despite the lack of modern innovation. In 2003, Canon released the EF-S lens mount to go with their entry level DSLR cameras (the Rebel Series). The cameras that support EF-S lenses will also support just EF lenses, but EF-only cameras (full-frame sensors) cannot support EF-S lenses.

55€

Photo Studio Light Flashes: (Just Photography)




What's included:

- Alienbees B1600 / 640Ws Strobe
- Alienbees B800 / 320Ws Strobe
- Photodiox Octobox
- Photodiox Softbox
- Softener Umbrellas
- TT860 Camera External Flash
- Strobe Triggers
- 220 to 120V Transform /PeakProtect
- 10m Extension
- 2 Tripods

Overview. The AlienBees™ are powerful, fast, accurate and versatile, with easy-to-use analog controls. The AlienBees™ self-contained studio flash units are available in three output models and five bold colors. Replacing Modeling Lamps/Flashtubes, and consistent casing.

AlienBees™ B800	AlienBees™ B1600
320 Ws	640 Ws
14,000 Ls	28,000 Ls
6 f-stops (full to 1/32)	6 f-stops (full to 1/32)
1 second	2 seconds
1/3300 second (at full power) 1/1650 second (at 1/32 power)	1/1800 second (at full power) 1/900 second (at 1/32 power)
1/1100 second (at full power) 1/550 second (at 1/32 power)	1/600 second (at full power) 1/300 second (at 1/32 power)
120 VAC, 50-60 HZ	120 VAC, 50-60 HZ
6 amps average	6 amps average
less than 6 volts	less than 6 volts
150 Watt supplied (150 Watt max.)	150 Watt supplied (150 Watt max.)
14mm single-ring tube	14mm single-ring tube
fits stands up to 5/8"	fits stands up to 5/8"
fits poles up to 3/8"	fits poles up to 3/8"
7AB/R 7-inch silver reflector (80° beam spread)	7AB/R 7-inch silver reflector (80° beam spread)
2.9 pounds	3.7 pounds
8.5" l x 7.875" h x 5.75" w	8.5" l x 7.875" h x 5.75" w

125€



NEEWER 2 x 660 PRO RGB LED Video Light Panel



- 2x LED lights
- 2x Tripods
- 8 Batteries
- Charger + Power Supply

50 W powerful and versatile RGB lighting set: the NEEWER 660 Pro RGB LED video light set has two powerful 50 W lights that provide flicker-free lighting, a color temperature of 3200 K $^{\sim}$ 5600 K, a dimming range of 0 $^{\sim}$ 100% and 360° RGB colors

Material: Aluminum Alloy.

Model: 660PRO.

LED Beads Quantity: 320 RGB bulbs,170 Cool color

beads, and 170 Warm color beads.

Power: 50W. CRI: 97+

Color temperature: 3200-5600K.

LUX: Brightness 100% (4400K) without diffuser:

7000Lux@0.5m, 2200Lux@1m.

Color: RGB+Bi-COLOR (cool color+warm color)

40€

Aputure Amaran 200d Kit x3 (Video Light)



What's included:

- 3x Amaran 200d Lights + Power Supply
- 3x Tripods
- Control Link app
- 2x GODOX Softbox 120 cm
- 2x Godox Lantern Softbox 65 cm
- 1x Aputure Fresnel
- 3x Standard Reflectors
- Carrying Case
- Filters + Clips
- 10m Extension Cable

Amaran 200d (Equivalent to 1500W) features a new light source design that increases spectral consistency and significantly improves light quality to deliver natural, pure colours for broadcast video, photography, TV production and studio film production. Improved SSI D56 (75 \rightarrow 89), CQS (94 \rightarrow 97), TLCI (96 \rightarrow 98) index, infinitely close to the sun's rays.

- 200W Point-Source LED Light
- Beam Angle: 105°, Dims 0-100%
- Color: 5600K, CRI/TLCI: 95/96
- Bluetooth Remote Controllable
- AC Power, Optional Battery
- 8 Built-In Customizable Effects
- Beam Angle, Native (COB): 105°
 Beam Angle, w/ Hyper Reflector: 55°
- Output Wattage: 200W
- Power Consumption: 250W
- Operating Current: 5.2A
- Operating Voltage, Battery: 48V/5.5A
- Operating Voltage, Power Supply Output:
- Operating Voltage, Power Supply Input: AC 100~240V 50/60HZ
- Operating Temperature: -20°C~45°C
- Control Methods: On-board, Sidus Link (Sidus MeshTM)
- Wireless Operating Range (Bluetooth): ≤
- Screen Type: LCD
- Firmware Upgradeable: Sidus Link OTA
- Cooling Method: Active Cooling
- Power Supply Head Cable: 3-pin XLR (3m)

160€

Neubildstudios GbR +49 (0) 177 - 6835 – 036 St -Nr: 162/161/71105 Tübingerstr. 3 80686, München, DE

Tube Led Lights for FX and Fill: Nanlite PavoTube T8-7x 8Kit



What's included:

- 8x Nanlite LED Tubes
- 8x Mini Tripods
- 8x Chargers + Chargestation
- 1x iPad Control Surface

The PavoTube T8-7X is an RGBWW LED pixel tube from Nanlite. The tubes feature the same customizable animated pixel effects as the PavoTube II X series. The compact housing with a diameter of 3.81cm and a built-in rechargeable battery make these LED tubes ideal for video productions and photo shoots. The T8-7X was developed for creative purposes, from light painting photography to use as an in-frame light for video productions

multifunctional RGBWW LED color effect light tubular shape (1 m)

white, colored light, 14 special effects incl. 10 segment effects

Mains or battery operation
Direct control or remote control
Color temperature from 2700 to 7500 K
Brightness adjustable from 0 to 100 % (app)
has a 1/4" connection thread
high color rendering index: CRI: 96, TLCI: 97
weighs only 280 g

30€

Audio Interface Tascam X8



What's included:

- Tascam Portacam X8 32bit 6 Chn /4 Phantom Powered Audio Recorder Interphase
- 2 14mm Microphones AB / XY
- Batteries AA x4
- Headphones for Monitoring
- 3x 3.5mm to XLR Cable
- 1x 3.5mm to Mini XLR (For Sync with Blackmagic Cameras)
- Micro SD 64GB
- USB Cable

Tascam X8 Portacapture is a high resolution, portable, multichannel recorder capable of capturing audio at 192kHz/32-Bit floating point to attain the highest level of detail in the recording. Designed for use in field recording, ENG, podcasts, interviews, music recording, and ASMR (Autonomous Sensory Meridian response), X8 can record external microphones, via the four XLR/TRS combination inputs; detachable, dual 14.6mm diameter A-B/X-Y microphone, or a mix of both.

A 3.5inch, colour touchscreen allows the user to navigate menus and adjust settings including the onboard DSP, which includes compressions, limiting, low-cut, noise gate, and automatic gain control, and reverb – to which there are six different room presets. Other functionality including pre-recording, autorecording, and dual recording modes can be accessed via the on screen menus. In addition to menu functionality, the touchscreen gives clear indication of channel input levels, output levels, file name, and record duration. Whilst the four combination (XLR/Jack) inputs allow the user to input microphones and instruments, including those that require 24/48V phantom power, there is an additional 3.5mm jack input to use as an audio input for an external camera. There

40€

Lavalier Microphone Wireless The Sennheisser ME 4 is a small clip-on microphone specially designed for speech applications in noisy environments. It is equipped with a capsule with a cardioid characteristic and is therefore largely resistant to feedback. Color: matt black. Digital 2.4 GHz and auto-pairing: SYNCO G1 (A1) Pro lavalier microphone wireless has a 2.4 GHz frequency What's included: spectrum and syncoder technology that avoids the 22€ Sennheisser ME4 Microphone + confusing range of UHF and provides a safe, stable and Accesories hassle-free audio system. It supports automatic Synco Wireless Audio System Stereo connection between TX and RX after power on and 3.5 to 3.5mm Cable easy operation when you need manual pairing. Case CVM-V20 SPECIFICATION **Boom Cardioid Microphone** Transducer Principle: Back Electronic Condenser Comica V20 Polar Pattern: Super Cardioid Max. SPL: ≥120dB Frequency Range: 100~12KHz THD: ≤1% Output Impedance: 680Ω±30% Dynamic Range: 120dB 45€ Sensitivity: -28dB / -38dB±3dB Signal to Noise Ratio: ≥55dB What's included: Battery Duration: 60 Hours Comica V20 Microphone Voltage: 3V XLR CABLE 10m Weight: 92g 2.5 m Boom pole Dimension: 133mm(L)*29.7mm(D)*64.3mm(H) Zeppelin Case Shotgun Mic Mount Windshield "Dead Cat" Cases Studio Blue Microphones Yeti X USB microphone The professional Yeti USB microphone impresses with blackout Microphone (Ideal for Podcasts) the custom recording software PreSonus and iZotope for advanced studio mastering and audio content at a professional level With automatic setup and sound processing for rich voices and music. Current consumption: 62 mA-203 mA Sample/bit rate: 48 kHz, 24 bit 12€ Capsules: 4 proprietary 14 mm condenser capsules Polar patterns: Cardioid, omnidirectional, figure-eight and stereo Frequency range: 20 Hz - 20 kHz Max. Sound pressure: 122 dB What's included: Dimensions (pulled out in holder): 11 cm x 12.2 cm x Yeti X USB Microphone 28.9 cm **Desk Stand** Weight (microphone and stand): 1.28 kg **USB** Cable Weight (microphone only):: 0.519 kg

Panoramic Drone DJI Mini Air 3 Pro 12MP, Type 1/1.3 (10 x 7.5mm) sensor Fly More Combo 24mm (equiv.) lens with a fixed F1.7 aperture Portrait shooting Ability to zoom up to 4X on video 4K/30p video H.264 codec and 100 Mbps bitrate Raw and JPEG image capture OcuSync 2.0 (O2) image transmission – 10 km (6.2 mi) **Downward Vision Sensing** Compatible with DJI RC remote Up to 38 or 51 minutes flight time 70€ 249g What's included: Drone Mini Air 3 Pro 3x Batteries + Charge station **4 Replacement Propellers Gimbal Protection Cap** DJI RC Drone 256 GB Micro SD Sandisk Xtreme Pro (Drone) 64 GB MicroSD Sandisk Ultra (RC) Filter Set x6 CPL, UV ND4,8, 16, 32 Sensor High Speed Drone DJI FPV Fly More 1/2,3-Zoll CMOS Combo, VR Goggles Effektive Pixel: 12 MP Objektiv Sichtfeld: 150° Äquivalente Brennweite: 14,66 mm Blende: f/2,8 Fokusmodus: Vollformat Fokusbereich: 0,6 m bis ∞ ISO 100-12.800 Verschlusszeit 1/50 - 1/8.000 s Fotomodi Einzelaufnahme What's included: Max. Bildgröße 150€ Drone DJI FPV 3840 × 2160 3x Batteries + Charge station Fotoformat **4 Replacement Propellers** JPEG **Propeller protection Case** Videoauflösung **Gimbal Protection Cap** 4K: 3.840×2.160@50/60fps DJI VR Goggles FHD: 1.920× 1.080@50/60/100/120fps 256 GB Micro SD Sandisk Xtreme Pro Videoformate MP4/MOV (MPEG-4 AVC/H.264, HEVC/H.265) (Drone) Max. Video-Bitrate 64 GB MicroSD Sandisk Ultra (Goggles) 120 MBit/s Filter Set x6 CPL, UV ND4,8, 16, 32 Farbmodus Standard, D-Cinelike *More than 250grams, License Mandatory Digitale Bildstabilisierung Unterstützt **Requires Operator + Supervisor both licensed, Verzerrungskorrektur according to Bundesluftamt. Unterstützt Unterstützte Dateisysteme exFAT (empfohlen) FAT32

Observations:

- All Prices include MWST 19%.
- Renting of the lease agreement and inventory list needs to be signed by hand.
- No Subleasing is allowed.
- Payment options: For freelancers Cash and Credit Card, for Companies Credit Card or Invoice.
- Minimum Heads-up time 2 days.
- Equipment Proof or Questions Free at installations (Please make appointment!)
 Not applies to Drones!
- Pick up and Return times Mo-Fr 7:00 19:00 / Sa 12:00-19:00 / Sun Closed (Please make appointment for In and Out!)
- Minimal rental time is one day, Implying Out from 9:00 and return before 19:00;
- WEEKEND RENTAL FEES:

Out Friday after 18:00, in Monday before 8:00 = 2 Day Out Saturday before 15:00, in Monday before 8:00 - 1.7 Day Out Saturday between 15:00-18:00, in Monday before 8:00 = 1.5 Day Out Saturday after 18:00, in Monday before 8:00 = 1 Day

EVENING RENTAL FEES

Out Mo-Sa after 18:00, in the following morning before 8:00 = -30% Discount

IMPORTANT: DELAY FINE

In after 9am (+1 hour Delay) = 0.25 Day Rental Price In Between 10-12:00 (+2-4 Hour Delay) = 0.5 Day Rental Price After 12:00 (+4-8 Hour Delay) = 1 Day Rental Price

- Please make sure to have done backup of your data before return, in no case Neubild GbR is responsible for data loss, all memories, disks and cards are formatted upon arrival.
- All Equipment is delivered 100% Charged and tested, unless special specified cases. (Ex: PowerStation).
- In case the Operating person of the equipment is External/Unknown to Neubildstudios GbR, there's a 15% compulsory insurance over the price of the equipment plus a 300€ deposit over the rental price. (Does not apply for Drone Equipment)
- Drone equipment only rented after License Verification, Flight route plan, and Caution deposit of 5x Day Rental, This condition does not apply if operated by Neubildstudios Crew.
- Computer Equipment for Postproduction Price list calculated individually according each project necessities and Schedule.

We wish you a pleasant and smooth shooting!

And ACTION!

Neubild GbR Team.